



Technical Data:

Material:

Insulator body (housing): PPS, UL94-V0, Color-Black.

Pin (outer sleeve): Brass, machined.

Tin plated: 50u" nickel, 200u" Tin plated..

Clip (6 finger): Beryllium copper.

Gold plated: 50u" nickel/full Gold-flashed.

Electrical:

Current rating: 3 Amps / contact max.

Contact resistance: 5mΩ / contact max.

Insulation resistance: > 1000 MΩ at V=100V Min.

Operating: 60V Ac/Dc.

Mechanical:

Operating temperature: Gold plated: -55°C to +125°C .

Tin plated: -40°C to +105°C .

Soldering temperature: +260°C 10s max.

No of contacts	Dim/mm A	Dim/mm B	No of contacts	Dim/mm A	Dim/mm B
1	2.0	2.0	21	40.0	42.0
2	2.0	4.0	22	42.0	44.0
3	4.0	6.0	23	44.0	46.0
4	6.0	8.0	24	46.0	48.0
5	8.0	10.0	25	48.0	50.0
6	10.0	12.0	26	50.0	52.0
7	12.0	14.0	27	52.0	54.0
8	14.0	16.0	28	54.0	56.0
9	16.0	18.0	29	56.0	58.0
10	18.0	20.0	30	58.0	60.0
11	20.0	22.0	31	60.0	62.0
12	22.0	24.0	32	62.0	64.0
13	24.0	26.0	33	64.0	66.0
14	26.0	28.0	34	66.0	68.0
15	28.0	30.0	35	68.0	70.0
16	30.0	32.0	36	70.0	72.0
17	32.0	34.0	37	72.0	74.0
18	34.0	36.0	38	74.0	76.0
19	36.0	38.0	39	76.0	78.0
20	38.0	40.0	40	78.0	80.0

Part No.

LSIP 200 - 1 × XX

No. of Contacts:
Single Row, XX:01~40

Pitch: 2.00mm

Series No: SIP Socket

REV	描述/REVISION	日期/DATE
A0	NEW DRAWING	2018.08.16

公差/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE

單位/Unit	品名/Title :
mm	SIP SOCKET 2.00mm Single Row Round Pin
比例/Scale	
Free	
Size	料號/Part No :
A4	LSIP200-1×XX

圖號/Drawing No :	製圖/DR.	審核/CHKD.	核准/APPD.
LIMSXX-A6(2.8)-2.0(S102-A6-1)	Mandy	Joe	Joe



鍊亨電子有限公司
LAI HENG TECHNOLOGY LTD.
TEL:(02) 8228-6487 FAX:(02) 8228-6486

圖號/Drawing No :	製圖/DR.	審核/CHKD.	核准/APPD.	張數/Sheet	REV.
LIMSXX-A6(2.8)-2.0(S102-A6-1)	Mandy	Joe	Joe	1 of 1	A0