



Technical Data:

Material:

Insulator body (housing): PBT, UL94-V0, Color-Black.

Pin (outsleeve): Brass, machined, CuZn38pb2.

Tin plated: > 40u" nickel, 100~150u" Tin Plated.

Clip (4 finger): Beryllium copper.

Gold plated: > 40u" nickel/full

Gold-flashed(0.4u"~1u").

Electrical:

Current rating: 3 Amps / contact max.

Insulation resistance: > 1000 MΩ at V=100V.

Operating: 60 Veff.

Mechanical:

Operating temperature: Gold plated: -55°C to +125°C .

Tin plated: -40°C to +105°C .

Soldering temperature: +200°C 10s max.

Part No.	BAR	No of contacts	Dim A	Dim B
LICS254R03006N	no bar	6	5.08	7.62
LICS254R03008N	no bar	8	7.62	10.16
LICS254R03010N	no bar	10	10.16	12.70
LICS254R03012N	no bar	12	12.70	15.24
LICS254R03014N	no bar	14	15.24	17.78
LICS254R03016N	no bar	16	17.78	20.32
LICS254R03018	with bar	18	20.32	22.86
LICS254R03020	with bar	20	22.86	25.40
LICS254R03022	with bar	22	25.40	27.94
LICS254R03024	with bar	24	27.94	30.48
LICS254R03028	with bar	28	33.02	35.56
JICS254R03032	with bar/2	32	38.10	40.64

公認/UNLESS OTHERWISE SPECIFIED TOLERANCES ARE			單位/Unit	品名/Title :
A0	NEW DRAWING	2018.08.16	mm	IC SOCKET 2.54mm Round Pin 0.3 Inch Wide
REV	概述/REVISION	日期/DATE	比例/Scale	料號/Part No :
			Free	LICS254R030XX X
			Size	圖號/Drawing No :
			A4	ISMXT1/03(S300-T1)



鍊亨電子有限公司

LAI HENG TECHNOLOGY LTD.
TEL:(02) 8228-6487 FAX:(02) 8228-6486

核加/APPD.	審核/CHKD.	製圖/DR.	張數/Sheet	REV.
7/6	Joe	Mandy	1 of 1	A0